

LED 3FT 12W Internal Tube



FEATURES

- Non-dimming
- Low thermal decay & maintenance
- No Mercury, UV or Lead
- 50,000 hours lifetime
- NSF rated for food zone (non-contact), splash zone and non-food zone

SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Supermarkets
- Factories
- Hospitals
- Office Buildings
- Airports

CONSTRUCTION:

Shatter proof glass housing with glass coating frosted lens.

ELECTRICAL:

Available as 120-277V input. -20°C to 50°C, -4°F to 122°F

OPTICAL SYSTEM:

197° beam angle.

INSTALLATION & MOUNTING:

Double ended Type B.

Single ended Type B. G13 base.

WARRANTY:

5-year limited warranty. Actual performance may differ as a result of end-user environment and application.



MODEL NUMBER	WATTAGE	LUMENS	EFFICACY	CRI	POWER FACTOR	THD	REPLACES
LOC-T83FT-12W40KDF B	12W	1,500LM	125LM/W	81	0.9	20%	32W – 36W
LOC-T83FT-12W50KDF B	12W	1,550LM	129.17LM/W	81	0.9	20%	32W – 36W

DLC Product ID:

- LOC-T83FT-12W40KDF B – PL4T67ES0NLA
- LOC-T83FT-12W50KDF B – PLCYRQNFL3JG

Series	Wattage	CCT Options	Size	Power
LOC	12W	4000K 5000K	3FT = 3 Foot	B = Type B