

## LED External Tube Series



### FEATURES

- Single ended Type C
- Wide beam full directional lighting
- IP40 rated
- Low thermal decay & maintenance
- No Mercury
- 50,000 hours lifetime

### SUITABLE APPLICATIONS

- Commercial buildings
- Hotels
- Conference rooms
- Schools
- Office Buildings

#### CONSTRUCTION:

Glass body

#### OPTICAL SYSTEM:

120° beam angle

#### WARRANTY:

3-month limited warranty. Actual performance may differ as a result of end-user environment and application.

#### ELECTRICAL:

Available as 120-277V input. -20°C to 50°C, -4°F to 122°F

#### INSTALLATION & MOUNTING:

Type C single ended.

#### CONTROLS & DIMMING:

Non-dimming.

| MODEL NUMBER          | WATTAGE | LUMENS    | EFFICACY  | CRI  | POWER FACTOR | THD   | REPLACES |
|-----------------------|---------|-----------|-----------|------|--------------|-------|----------|
| LOD-EXT82FD-10W40KF-1 | 10W     | 1,258.3LM | 123.3LM/W | 82.5 | 0.91         | 12.6% | 25W      |
| LOD-EXT82FD-10W50KF-1 | 10W     | 1,311.1LM | 129.8LM/W | 82.7 | 0.92         | 13.2% | 25W      |
| LOD-EXT84FD-15W50KF-1 | 15W     | 1,919.4LM | 127.9LM/W | 82.4 | 0.92         | 13.4% | 32W      |